

Tractor Implement

Plow	
Model	Mating power
Mounted two-furrow plow LXT 12-2-20	18-20 HP
Light-duty triparted rolling coulter 1LYQ-320	25-40 HP
Mounted three-furrow plow LXT 25-3-20	25 HP
Light-duty mounted three-furrow plow 1LQ-325	30 HP
Light-duty mounted four-furrow plow 1LQ-425	40 HP
Triparted rolling coulter 1LY-325	50 HP
Medium mounted three-furrow plow 1L-330	50 HP
Four-component rolling coulter 1LY-425	60-120 HP
Mounted five-furrow plow 1L-527	65 HP
Amplitude-modulation three-furrow plow 1L-335	70-75 HP
Amplitude-modulation four-furrow plow 1LT-435	80-120 HP
Light-duty triparted rolling coulter 1LYQ-315	18-20 HP
Mounted amplitude-modulation hydraulic roll-over plow 1LF-335	70-90 HP
Mounted amplitude-modulation plow 1LYF-435	80-90 HP
Heavy-duty mounted five-furrow plow 1LD-535	100-120 HP

Rotary Farming Machine	
Model	Mating power
1GQN-125	25 HP
1GQN-160KD	40 HP
1GQN-200KH	70-80 HP
1GQN-230K-QY	80-90 HP
1GQN-250K	90-100 HP
1GQN280K	110-120 HP
1GQN300K	130-140 HP
1GQN350K	140-180 HP

Harrow	
Model	Mating power
Disk harrow IBQ-5.0	80-90 HP

Power driven harrow IBD-3.4	80-90 HP
14-piece mounted light harrow 1BQX-1 .3	18-20 HP
16-piece mounted light harrow 1BQX-1 .5	25 HP
18-piece mounted light harrow 1BQX-1 .7	30-40 HP
18-piece medium harrow 1BJX-2.0	50 HP
22-piece medium harrow 1BJX-2.4	65 HP
20-piece hydraulic offset heavy harrow 1BZ-2.0	70-80 HP
24-piece hydraulic offset heavy harrow 1BZ-2.5	100-120 HP

Seed Drill	
Model	Mating power
Fertilizer application seed drill 2BFXZ-24	80-120 HP
No tillage covering vacuum planter 2BQM-6A	80-90 HP
Seed drill 2BXD-12	18-20 HP
Fertilizer application seed drill 2BFT-12	25-30 HP
Mounted seed drill 2B-16	40 HP
Mounted fertilizer application seed drill 2BFX-16	50-60 HP
Mounted seed drill 2BX-24	70-80 HP
Fertilizer application seed drill 2BFX-24	100-120HP

Tractor Trailer			
Model	YTO-7CX-3	YTO-7CX-5	YTO-7CX-6
Rated load	3000 kg	5000 kg	6000 kg
Deadweight	1280kg	2500kg	2700kg
Overall dimensions L×W×H	4000×1740×2150 mm	6200×2300×2600 mm	6350×2200×2600 mm
Carriage capacity	2.4 m3	4.7m3	5.42m3
Tread	1300 mm	1670 mm	1670 mm
Wheelbase	1700 mm	2180 mm	2780 mm
Ground clearance from the towing point	530 mm	805 mm	805 mm
Number of wheels	4	4	4
Tyre specifications	750-16	900-20	900-20
Brake type	Air brake	Air brake	Air brake
Steering type	Centerless rotating plate	Centerless rotating plate	Centerless rotating plate

Suspension type	Plate spring elastic suspension	Plate spring elastic suspension	Plate spring elastic suspension
Tilting type	Tilting to the left and to the right	Tilting to the left and to the right	Tilting to the left and to the right
Max. angle of overturn	$\geq 45^\circ$	$\geq 45^\circ$	$\geq 45^\circ$
Tractor engine power	20-40 HP	50-90 HP	50-90 HP

Stalk Chopper		
Model	1JH165Q	1JH180
Mating power	60-70 HP	70-80 HP

Mini Cultivator, Tiller		
Model	1WG105	1WG135
Mating power	5.44 HP	8.57 HP

Snow Plow	
Snow removal device model	Mating power
SX150	20-40 HP
SX165	40-60 HP
SX180	60-80 HP
SX210	80-90 HP
Snow shovel model	Mating power
TX150	20-40 HP
TX165	40-60 HP
TX180	60-80 HP
TX210	80-90 HP

Binding Machine		
Model		MRB0850
Mating power	HP	25-50
PTO speed	r/min	540
Working speed	km/h	2.5
Weight	kg	390
Dimensions(L×W×H)	mm	1150×1300×1200
Binding width	cm	80

Mower		
Cutting width	m	1
Cutting height	cm	10-30
Mating power	HP	25-30
Linkage type		3 point, semi attached
Package size (L×W×H)	mm	1450×1250×620(2 pieces)
Single piece weight	kg	235
Total weight	kg	540(2 pieces)